



**THE FIRST CHOICE OF FIRST RESPONDERS**

# APX™ 7000 MULTIBAND PORTABLE RADIO

On surveillance, on border patrol or on a multi-agency response, you want a radio that keeps you connected, no matter how loud the background noise, harsh the weather or long the hours. You depend on a ruggedly reliable portable with crystal-clear communication so every word is heard. You need a multiband radio so interoperable, multiple federal, state and local agencies can communicate and collaborate seamlessly together – without having to carry two radios.

Working with public safety and federal personnel around the world, we developed the smallest multiband portable on the market: the APX™ 7000. We engineered our radio with their requests in mind – from easy-to-use design and seamless interoperability to best-in-class audio. The result is an interoperable multiband radio that is 50% louder than comparable radios in its class.\*

## **INTEROPERATE IN AN INSTANT**

Rushing to a fire or reporting from a covert operation, you don't want to carry two radios in order to communicate. That's why the APX 7000 is so valuable. It performs across

multiple digital and analog networks and operates in any of two bands (700/800 MHz, VHF and UHF R1, UHF R2) for instant interoperability. Now you can efficiently manage mission critical voice and data in any environment – and significantly improve your safety and response time.

## **HEAR EVERY WORD**

The frenzy of city streets. The blare of sirens. The whine of equipment. Background noise can block communications. But with a dual-sided two-microphone design for exceptional noise-canceling, dual speakers for the loudest, clearest audio available and the latest AMBE digital voice vocoder, the APX 7000 cuts through the clamor – so every word is heard and every message is understood, everywhere you go.

## **FUTURE-READY WHEN YOU ARE**

How can you protect your radio investment and make sure your new purchases are easily updated as technology evolves? Every APX 7000 radio is backward and forward compatible, meets current P25 standards and is future-ready to support new technology and data applications. So you can achieve your interoperability objectives— whether upgrading an existing system or designing a new one—at your own pace.

\*Based on results of controlled engineering tests



# APX 7000 PROJECT 25 MULTIBAND PORTABLE RADIO

## FEATURES AND BENEFITS:

- Available in 700-800 MHz, VHF, UHF Range 1, and UHF Range 2 bands
- Optional multiband operation
- Trunking standards supported:
  - Clear or digital encrypted ASTRO®25 Trunked Operation
  - Capable of SmartZone®, SmartZone Omnilink, SmartNet®
- Analog MDC-1200 and Digital APCO P25 Conventional System Configurations
- Narrow and wide bandwidth digital receiver\* (6.25 kHz equivalent / 12.5 kHz / 30 kHz / 25 kHz)
- Embedded digital signaling (ASTRO & ASTRO 25)
- Seamless wideband scan
- Integrated Voice & Data
- Integrated GPS/GLONASS for outdoor location tracking
- Software Key
- Intelligent Lighting
- Radio Profiles
- Unified Call List (Dual Display model only)
- Expansion Slot
- Micro SD removable memory card
- User programmable voice announcement
- Meets Applicable MIL-STD-810C, D, E, F, and G IP67 standard\*\*\*\*

Custom recessed label areas

Superior Audio Features:

- 1W high audio speaker
- Dual speakers (Dual Display model only)
- Dual microphones
- 2-mic noise canceling technology

Utilizes Windows XP, Vista, Windows 7 and 8 Customer Programming Software (CPS)\*\*\*

- Supports USB communications
- Built in FLASHport™ support

Full portfolio of accessories including IMPRES batteries, chargers and audio devices

Mission Critical Wireless Bluetooth\*\*

## OPTIONAL FEATURES:

- Enhanced Encryption capability
- Programming Over Project 25
- Over the Air Rekey
- Text Messaging
- Man Down
- Submersible to 2 meters for 2 hours (with Rugged Option)
- Public Safety Yellow and High Impact Green housing options

\* Per the FCC Narrowbanding rules, new products (APX7000 UHF R1 with UHF R2 combination) submitted for FCC certification after January 1, 2011 are restricted from being granted certification at 25KHz for United States - State & Local Markets only.

\*\* Compatible with BT 2.1 HSP, PAN, DUN and SPP BT Profiles

\*\*\* CPS version R12.00.00 and greater ordered after June 2014 will only support Windows 7 and 8

\*\*\*\* Radios meet industry standards (IPx7) for submersion.

## TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS

|  | 700 MHz                          | 800 MHz                    | VHF                        | UHF Range 1                | UHF Range 2                |
|--|----------------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| Frequency Range/Bandsplits                                       | 763-776 MHz<br>793-806 MHz       | 806-824 MHz<br>851-870 MHz | 136-174 MHz                | 380-470 MHz                | 450-520 MHz                |
| Channel Spacing  | 25/12.5 kHz                      | 25/12.5 kHz                | 30/25/12.5 kHz             | 25/20/12.5 kHz             | 25/12.5 kHz                |
| Maximum Frequency Separation                                     | Full Bandsplit                   | Full Bandsplit             | Full Bandsplit             | Full Bandsplit             | Full Bandsplit             |
| Rated RF Output Power Adj <sup>i</sup>                           | 1-2.5 Watts                      | 1-3 Watts                  | 1-6 Watts                  | 1-5 Watts                  | 1-5 Watts                  |
| Frequency Stability <sup>1</sup><br>(-30°C to +60°C; +25°C Ref.) | ±0.8 ppm                         | ±0.8 ppm                   | ±0.8 ppm                   | ±0.8 ppm                   | ±0.8 ppm                   |
| Modulation Limiting <sup>1</sup>                                 | ±5 kHz / ±4 kHz / ±2.5 kHz       | ±5 kHz / ±4 kHz / ±2.5 kHz | ±5 kHz / ±4 kHz / ±2.5 kHz | ±5 kHz / ±4 kHz / ±2.5 kHz | ±5 kHz / ±4 kHz / ±2.5 kHz |
| Emissions (Conducted and Radiated) <sup>1</sup>                  | -75 dB                           | -75 dB                     | -75 dB                     | -75 dB                     | -75 dB                     |
| Audio Response <sup>1</sup>                                      | +1, -3 dB                        | +1, -3 dB                  | +1, -3 dB                  | +1, -3 dB                  | +1, -3 dB                  |
| FM Hum & Noise   | 25 kHz -48 dB<br>12.5 kHz -46 dB | -47 dB<br>-45 dB           | -47 dB<br>-45 dB           | -47 dB<br>-45 dB           | -47 dB<br>-45 dB           |
| Audio Distortion <sup>1</sup>                                    | 0.60 %                           | 1 %                        | 0.50 %                     | 0.50 %                     | 0.50 %                     |

## BATTERIES FOR APX 7000

| Battery Capacity / Type                   | Dimensions (HxWxD)    | Weight   | Battery Part Number | Battery Capacity |
|---|-----------------------|----------|---------------------|------------------|
| Li-Ion IMPRES2 2300 mAh IP68*             | 3.39" x 2.34" x 1.65" | 6.53 oz  | NNTN8930            | 2300 mAh         |
| Li-Ion IMPRES 4200 mAh (IP67)             | 5.12" x 2.34" x 1.65" | 11.29 oz | NNTN7034            | 4200 mAh         |
| Li-Ion IMPRES2 4500 mAh TIA 4950-A IP68** | 5.12" x 2.34" x 1.65" | 11.29 oz | NNTN8921            | 4500 mAh         |
| NiMH IMPRES 2100 mAh (IP67)               | 5.07" x 2.34" x 1.57" | 11.82 oz | NNTN7037            | 2100 mAh         |
| NiMH IMPRES 2100 mAh (Rugged)             | 5.07" x 2.34" x 1.57" | 11.82 oz | NNTN7573            | 2100 mAh         |
| Li-Ion IMPRES 2150 mAh IP67               | 3.39" x 2.34" x 1.45" | 5.0 oz   | PMNN4403            | 2150 mAh         |
| Li-Ion IMPRES2 2300 mAh TIA 4950-A IP68** | 3.39" x 2.34" x 1.65" | 6.53 oz  | NNTN8930            | 2300 mAh         |
| Li-Ion IMPRES2 2650 mAh TIA 4950-A IP68** | 3.39" x 2.34" x 1.65" | 5.82 oz  | NNTN8930            | 2650 mAh         |

\* Standard shipping battery

\*\* HAZ LOC approval only available on 7/800 MHz & VHF Band combinations.

## RECEIVER - TYPICAL PERFORMANCE SPECIFICATIONS

|  |                  | 700 MHz        | 800 MHz        | VHF            | UHF Range 1    | UHF Range 2    |
|--|------------------|----------------|----------------|----------------|----------------|----------------|
| Frequency Range/Bandsplits                                       |                  | 763-776 MHz    | 851-870 MHz    | 136-174 MHz    | 380-470 MHz    | 450-520 MHz    |
| Channel Spacing  |                  | 25/12.5 kHz    | 25/12.5 kHz    | 30/25/12.5 kHz | 25/12.5 kHz    | 25/12.5 kHz    |
| Maximum Frequency Separation                                     |                  | Full Bandsplit | Full Bandsplit | Full Bandsplit | Full Bandsplit | Full Bandsplit |
| Audio Output Power at Rated <sup>1</sup>                         |                  | 1000 mW        | 1000 mW        | 1000 mW        | 1000 mW        | 1000 mW        |
| Frequency Stability <sup>1</sup><br>(-30°C to +60°C; +25°C Ref.) |                  | ±0.8 ppm       | ±0.8 ppm       | ±0.8 ppm       | ±0.8 ppm       | ±0.8 ppm       |
| Analog Sensitivity <sup>3</sup>                                  | 12 dB SINAD      | 0.250 µV       | 0.250 µV       | 0.216 µV       | 0.234 µV       | 0.234 µV       |
| Digital Sensitivity <sup>4</sup>                                 | 1% BER           | 0.347 µV       | 0.333 µV       | 0.277 µV       | 0.307 µV       | 0.307 µV       |
|  | 5% BER           | 0.251 µV       | 0.251 µV       | 0.188 µV       | 0.207 µV       | 0.207 µV       |
| Selectivity <sup>1</sup>   | 25 kHz channel   | 75.7 dB        | 75.7 dB        | 79.3 dB        | 78.3 dB        | 78.3 dB        |
|  | 12.5 kHz channel | 67.5 dB        | 67.5 dB        | 70 dB          | 68.1 dB        | 67.5 dB        |
| Intermodulation  |                  | 80 dB          | 80 dB          | 80.5 dB        | 80.2 dB        | 80.2 dB        |
| Spurious Rejection   |                  | 76.6 dB        | 76.6 dB        | 93.2 dB        | 80.3 dB        | 80.3 dB        |
| FM Hum & Noise   | 25 kHz           | -54 dB         | -54 dB         | -53.8 dB       | -53.5 dB       | -53.5 dB       |
|  | 12.5 kHz         | -48 dB         | -48 dB         | -48 dB         | -47.4 dB       | -47.4 dB       |
| Audio Distortion <sup>1</sup>                                    |                  | 0.9 %          | 0.9 %          | 1.20 %         | 0.91 %         | 0.91 %         |

## RADIO MODELS

### Model 1.5 Top Display

|                           |  |                    |                |
|---------------------------|--|--------------------|----------------|
| Display                   | Full bitmap monochromatic LCD display ■ 1 line text, 8 characters ■ 1 line of icons ■ No menu support ■ Multi-color backlight  |                    |                |
| Keypad                    | None   |                    |                |
| Channel Capacity          | 1200   |                    |                |
| FLASHport Memory          | 64 MB  |                    |                |
| 700/800 MHz (763-870 MHz) | Primary QA00569  | Secondary QA00573  | Keypad QA00577 |
| VHF (136-174 MHz)         | Primary QA00570  | Secondary QA00574  | Keypad QA00577 |
| UHF Range 1 (380-470 MHz) | Primary QA00571  | Secondary QA00575  | Keypad QA00577 |
| UHF Range 2 (450-520 MHz) | Primary QA00572  | Secondary QA00576  | Keypad QA00577 |
| Buttons & Switches        | Large PTT button ■ Angled On/Off Volume knob ■ Orange emergency button ■ 16 position top mounted rotary switch ■ 2-position concentric switch ■ 3-position toggle switch ■ 3 programmable side buttons ■ Multi-color backlight |                    |                |
| Embedded                  | GPS<br>LED   | Yes<br>Multi-color |                |

### Model 3.5 Dual Display

|                           |  |                    |                |
|---------------------------|--|--------------------|----------------|
| Display                   | Top display plus full bitmap color display ■ LCD display ■ 4 lines text, 14 characters ■ 2 lines of icons ■ 1 menu line, 3 menus   |                    |                |
| Keypad                    | Multi-color backlight ■ Full Keypad ■ 3 soft keys ■ 4-direction navigation key ■ 4x3 keypad ■ Home and Data buttons  |                    |                |
| Channel Capacity          | 3000   |                    |                |
| FLASHport Memory          | 64 MB  |                    |                |
| 700/800 MHz (764-870 MHz) | Primary QA00569  | Secondary QA00573  | Keypad QA00577 |
| VHF (136-174 MHz)         | Primary QA00570  | Secondary QA00574  | Keypad QA00577 |
| UHF Range 1 (380-470 MHz) | Primary QA00570  | Secondary QA00574  | Keypad QA00577 |
| UHF Range 2 (450-520 MHz) | Primary QA00572  | Secondary QA00576  | Keypad QA00577 |
| Buttons & Switches        | Large PTT button ■ Angled On/Off Volume knob ■ Orange emergency button ■ 16 position top mounted rotary switch ■ 2-position concentric switch ■ 3-position toggle switch ■ 3 programmable side buttons ■ Multi-color backlight |                    |                |
| Embedded                  | GPS<br>LED   | Yes<br>Multi-color |                |

### Transmitter Certification

|                      |   |
|----------------------|---|
| VHF – 700/800 MHz    | AZ489FT7036 (136-174 MHz and 764-869 MHz) |
| UHF R1 – 700/800 MHz | AZ489FT7040 (380-470 MHz and 764-869 MHz) |
| UHF R1 – VHF         | AZ489FT4886 (380-470 MHz and 136-174 MHz) |
| UHF R2 – 700/800 MHz | AZ489FT7042 (450-520 MHz and 764-869 MHz) |
| UHF R2 – VHF         | AZ489FT4893 (450-520 MHz and 136-174 MHz) |
| Bluetooth            | AZ489FT6000                               |
| BT Freq Range        | 2402-2480 MHz                             |

### FCC Emission Designators

|                          |   |
|--------------------------|---|
| FCC Emission Designators | 11K0F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 20K0F1E* |
|--------------------------|---|

### Power Supply

|              |   |
|--------------|---|
| Power Supply | One rechargeable 2900 mAh Li-Ion Battery Standard (NNTN7038), with alternate battery options available. |
|--------------|---|

\* Per the FCC Narrowbanding rules, new products (APX7000 UHF R1 with UHF R2 combination) submitted for FCC certification after January 1, 2011 are restricted from being granted certification at 25KHz for United States - State & Local Markets only.

## GPS SPECIFICATIONS

|                       |                               |
|-----------------------|-------------------------------|
| Channels              | 12                            |
| Tracking Sensitivity  | -151 dBm                      |
| Accuracy <sup>5</sup> | <10 meters (95%)              |
| Cold Start            | <60 seconds (95%)             |
| Hot Start             | <10 seconds (95%)             |
| Mode of Operation     | Autonomous (Non-Assisted) GPS |

## DIMENSIONS OF THE RADIOS WITHOUT BATTERY

|                                      | Inches  | Millimeters |
|--------------------------------------|---------|-------------|
| Length                               | 6.29    | 159.7       |
| Width Push-To-Talk button            | 2.31    | 58.6        |
| Depth Push-To-Talk button            | 1.34    | 34.0        |
| Width Top                            | 2.98    | 75.6        |
| Depth Top                            | 1.6     | 40.5        |
| Depth Bottom of Battery              | 1.65    | 41.7        |
| Weight of the radios without battery | 12.2 oz | 346 g       |

## PORTABLE MILITARY STANDARDS 810 C, D, E, F & G

|                   | MIL-STD 810C |                 | MIL-STD 810D |             | MIL-STD 810E |             | MIL-STD 810F |                     | MIL-STD 810G |               |
|-------------------|--------------|-----------------|--------------|-------------|--------------|-------------|--------------|---------------------|--------------|---------------|
|                   | Method       | Proc./Cat.      | Method       | Proc./Cat.  | Method       | Proc./Cat.  | Method       | Proc./Cat.          | Method       | Proc./Cat.    |
| Low Pressure      | 500.1        | I               | 500.2        | II          | 500.3        | II          | 500.4        | II                  | 500.5        | II            |
| High Temperature  | 501.1        | I, II           | 501.2        | I/A1, II/A1 | 501.3        | I/A1, II/A1 | 501.4        | I/Hot, II/Basic Hot | 501.5        | I/A1, II/A2   |
| Low Temperature   | 502.1        | I               | 502.2        | I/C3, II/C1 | 502.3        | I/C3, II/C1 | 502.4        | I/C3, II/C1         | 502.5        | I/C3, II/C1   |
| Temperature Shock | 503.1        | 1 Proc          | 503.2        | I/A1C3      | 503.3        | I/A1C3      | 503.4        | I                   | 503.5        | I/C           |
| Solar Radiation   | 505.1        | II              | 505.2        | I           | 505.3        | I           | 505.4        | I                   | 505.5        | I/A1          |
| Rain              | 506.1        | I, II           | 506.2        | I, II       | 506.3        | I, II       | 506.4        | I, III              | 506.5        | I, III        |
| Humidity          | 507.1        | II              | 507.2        | II          | 507.3        | II          | 507.4        | 1 Proc              | 507.5        | II/Aggravated |
| Salt Fog          | 509.1        | 1 Proc          | 509.2        | I           | 509.3        | I           | 509.4        | 1 Proc              | 509.5        | 1 Proc        |
| Blowing Dust      | 510.1        | I               | 510.2        | I           | 510.3        | I           | 510.4        | I                   | 510.5        | I             |
| Blowing Sand      |              | 1 Proc          | 510.2        | II          | 510.3        | II          | 510.4        | II                  | 510.5        | II            |
| Submersion        | 512.1        | I               | 512.2        | I           | 512.3        | I           | 512.4        | I                   | 512.5        | I             |
| Vibration         | 514.2        | VIII/F, Curve-W | 514.3        | I/10, II/3  | 514.4        | I/10, II/3  | 514.5        | I/24                | 514.6        | I/24          |
| Shock             | 516.2        | I, III, V       | 516.3        | I, V, VI    | 516.4        | I, V, VI    | 516.5        | I, V, VI            | 516.6        | I, V, VI      |
| Shock (Drop)      | 516.2        | II              | 516.2        | IV          | 516.4        | IV          | 516.5        | IV                  | 516.6        | IV            |

## ENCRYPTION

|                                   |  |
|-----------------------------------|--|
| Supported Encryption Algorithms   | ADP, AES, DES, DES-XL, DES-OFB, DVP-XL   |
| Encryption Algorithm Capacity     | 8  |
| Encryption Keys per Radio         | Module capable of storing 1024 keys. Programmable for 128 Common Key Reference (CKR) or 16 Physical Identifier (PID) |
| Encryption Frame Re-sync Interval | P25 CAI 300 mSec   |
| Encryption Keying                 | Key Loader   |
| Synchronization                   | XL – Counter Addressing<br>OFB – Output Feedback   |
| Vector Generator                  | National Institute of Standards and Technology (NIST) approved random number generator                               |
| Encryption Type                   | Digital  |
| Key Storage                       | Tamper protected volatile or non-volatile memory   |
| Key Erasure                       | Keyboard command and tamper detection  |
| Standards                         | FIPS 140-2 Level 3<br>FIPS 197   |

## ENVIRONMENTAL SPECIFICATIONS

|   |  |
|---|--|
| Operating Temperature                                     | -30°C / +60°C  |
| Storage Temperature <sup>7</sup>                          | -40°C / +85°C  |
| Humidity  | Per MIL-STD  |
| ESD   | IEC 801-2 KV   |
| Water and Dust Intrusion                                  | Mil Std 512.X, Delta - T   |
| Hazardous Location/<br>Intrinsic Safety (IS) <sup>8</sup> | Class I, Division 1, Group D;<br>Class II, Division 1, Group E, F, G;<br>Class III, Hazardous (Classified) Locations |

Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.

<sup>1</sup> Measured in the analog mode per TIA / EIA 603 single-tone method under nominal conditions

<sup>2</sup> When used with an HazLoc approved radio.

<sup>3</sup> Measured conductively in analog mode per TIA / EIA 603 under nominal conditions

<sup>4</sup> Measured conductively in digital mode per TIA / EIA IS 102.CAAA under nominal conditions

<sup>5</sup> Accuracy specs are for long-term tracking (95th percentile values >5 satellites visible at a nominal -130 dBm signal strength)

<sup>6</sup> For rugged models only

<sup>7</sup> Temperatures listed are for radio specifications. Battery storage is recommended at 25°C, ±5°C to ensure best performance

<sup>8</sup> Only when ordered with HAZ LOC approved battery. Only available on 7/800 MHz & VHF band combinations.

Motorola Solutions, Inc. 1301 East Algonquin Road Schaumburg, Illinois 60196, U.S.A. 800-367-2346  
[motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2016 Motorola Solutions, Inc. All rights reserved. 06-2016